WATER PROBE

3010-H2OS180-EN1751

FLAIR ELECTRONICS

PROTECT AGAINST FLOODING

The Flair Water Probe, P/N 3010-H2OS180-EN1751 is 3" Diameter X 3/4" Tall and works with the Inovonics EN1751 transmitter to detect leaking or flooding water or other electrically conductive fluid. The Water Probe comes with 15 Feet leads and wires directly to the EN1751. Probe is heavy enough to sit on ground but can be screwed down with #8 screw through center hole too. When a conductive liquid rises 1/16" bridging two of the four probes the loop will short triggering an alarm. Wires are supervised and will trigger tamper alarm if cut or disconnected.

INSTALL WHERE EVER LEAKS CAN OCCUR

*Sump Pumps
*Dishwashers
*Washing Machines
*Industrial Tanks
*Water Heaters
*Refrigerators
*Air Conditioners
*Industrial Equipment

TRANSMITTER SPECIFICATIONS:

Typical Battery Life: 3 - 5 years
EchoStream Frequency: 902-928 MHz
Check-In Time Frequency: 60 minutes
Loop: Supervised

powered by inovonics®

FLAIR MODEL 582-1015 WIRELESS ANNUNCIATOR - For multiple zone applications and local alarm notification use the Flair Model 582-1015-24 or -32 Wireless Annunciator with built-in Inovonics receiver. Each zone monitors 24 or 32 individual Water Probes, P/N 3010-H2OS-EN1752. When water or any conductive liquid is detected by a Water Probe a Red LED on the Model 582 Annunciator and a low level adjustable Sounder (approx. 85db max.) will latch On. Two separate Push Buttons on side of Annunciator are used to silence Sounder and, once EN1751 Transmitter is secure again, reset zone.